

## MANUAL INTERMEDIATE PROOFER Model COMPACT LOFT

### USE

- Machine to rest dough pieces and make the link between the hydraulic divider and the moulder
- Possibility of an integrated vertical moulder only (option)

### CAPACITY (\*)

59 balance pans with a capacity of 472 baguettes and 413 breads.

(\*) : Standard information that can change, depending on the dough nature.



Manuel group : diva + COMAPCT LOFT + Trégor Tradition

### FEATURES

**Free-standing structure made of 40/40 and non-buckling steel tubes.**

The non-buckling frame prevents the balance pans from overtightening risks.

**Channels made of Nyltex®.**

Prevent dough balls from sticking and reduce the flouring (except at the start in order to « season » the channels.)  
Machine or hand washable for the best hygiene and reduced cleaning costs.

**Machine on castors.**

Non-buckling frame easy to move thanks to the castors.  
The area cleaning is easier, as well as the machine movings without any risk of twisting the frame or changing the adjustments.

**Balance pan turnaround and emptying system with a release mechanism.**

Allows to use all the balance pans.  
Allows to handle dough balls that musn't go in the moulder.

**Advance of balance pans by pedal,**

while you remove doughs from the divider.

**Work is carried out at an ergonomic height.**

No more handling of boards, it is possible to work at the same height, at your rythm and more comfortably.

**Possible manual advance in case of power cut.**

This enables to handle dough balls in order to shape them.

**Dibon® - composite casing**

This casing easy to remove, enables to have a quick access inside the machines if necessary.

**Possibility of an integrated vertical moulder.**

Easy lay-out and saving of space.

### OPTIONS

- Folding tablet covered with felt (for the dough ball rounding.)
- UV Lamps

## PRESENTATION



- 1- Electrical box  
2- Emptying belt

## WEIGHT

Net weight : 450 Kg (992 lb)

*Packaging on slatted outer carton pallet two way :*

Gross weight : 470 Kg (1036 lb)

Dimensions (Length X Width X Height) :  
250 x 150 x 180 cm (8.02 x 4.92 x 5.9 ft)

*Packaging on slatted wood box pallet two way :*

Gross weight : XX Kg

Dimensions (Length X Width X Height) :  
XXX

(\* Maritime full box, treated wood)

## HYGIENE-SECURITY

The COMPACT LOFT intermediate proofer proofer is in accordance with :

- 89/392 CEE, the directive on hatches.
- The labour regulations.

## OVERALL DIMENSIONS



	H	D	W (floor)
COMPACT LOFT	229 cm 7.53 ft	137 cm 4.49 ft	166 cm 5.44 ft

## ELECTRIC SPECIFICATIONS

- 380 Volts / 50 Hz / 0,4 Kw maxi
  - 380 Volts / 60 Hz / 0,4 Kw maxi
  - 220 Volts / 50 Hz / 0,4 Kw maxi
  - 220 Volts / 60 Hz / 0,4 Kw maxi
- Power supply: 4 m cable with plug sorting TRI + T + N*

 **Mécapâte**  
**MERAND**  
*Le Maître d'œuvre de la pâte*

Distributed by :