

PAXO MOUV

OBLIQUE AXIS MIXER

WITH REMOVABLE BOWL

USE

The PAXO Mouv mixer can handle all types of dough, including highly hydrated doughs.

Thanks to its removable bowl on a trolley, it allows easy transfer to a lifter or bulk resting of the dough directly in the bowl.

CAPACITIES

Model	Bowl volume mini/maxi (in liters)	Flour volume mini/maxi (in kg)	Dough weight (in kg)
Paxo Mouv 30	10/30	18,7/50	80
Paxo Mouv 45	15/45	25/75	120
Paxo Mouv 60	20/60	33/100	160

Information provided for reference only. Values may vary depending on the dough type.



FEATURES

- One-piece steel frame with food-grade epoxy coating, ensuring robustness and durability.
- Cast aluminum kneading arm with manual lifting for simple and ergonomic handling.
- Removable stainless steel bowl with rounded edges, equipped with a manual brake for secure positioning.
- Two electronic timers with dual digital display (up to 20 minutes each) and programmed time recall.
- Option to use a single timer for continuous operation with automatic stop at the end of the cycle.
- Timer masking function for uninterrupted, unlimited operation.

- Two speeds on both timers, with automatic shift from first to second speed in AUTO mode.
- Sealed control panel integrated into the frame for enhanced safety.
- Tilting head as standard (pivoting on two bearings).
- Full safety cover equipped with an access hatch for practical and safe use.
- Secure tilting stainless steel cover, saving space: once opened, it fully clears access to the bowl as the guard tilts backward.

OPTION

- Additional Bowl

Z.I. de la Turbanière
BRECE • 35530 • FRANCE

+33 (0)2 99 04 15 30 - salesdpt@merand.fr - www.merand.fr

FEATURES

MODEL	KNEADING ARMS		STAINLESS STEEL BOWL		
	1 ST SPEED	2 ND SPEED	CAPACITY (IN LITRES)	BOWL DIAMETERS (IN MM)	BOWL BRAKE
Paxo Mouv 30	48 rpm at full load	72 rpm at full load	170	800	Manual
Paxo Mouv 45			230	900	
Paxo Mouv 60			330	1 000	

PRESENTATION



DIMENSIONS

MODEL	LENGTH (IN MM)	HEIGHT (IN MM)	DEPTH (IN MM)	DEPTH WITH IN OPEN COVER (IN MM)	WEIGHT (IN KG)
Paxo Lift 30	1 260	1 295	1 130	1 270	500
Paxo Lift 45	1 360		1 155	1 295	520
Paxo Lift 60	1 460		1 180	1 320	540

ELECTRICAL SPECIFICATIONS

Maximum power (at 2nd speed): 5.5 kW
Voltage: 3-phase 400 V + N + PE

SECURITY

The mixer complies with:

- Machinery Directive 2006/42/EC
- Labour Code

**Z.I. de la Turbanière
BRECE • 35530 • FRANCE**
+33 (0)2 99 04 15 30 - salesdpt@merand.fr - www.merand.fr